

LINEARlight FLEX Protect ADVANCED

– LED modules for professional and industrial applications



Product family features

- Flexible and cuttable LED strip
- Luminous flux: up to 420 lm/m
- Type of protection: IP67
- Dimmable with PWM technology
- Fine White (3.5 SDCM)
- Salt mist proof

Product family benefits

- Very long for seamless bands of light
- Great design freedom thanks to flexibility and cuttability of module
- High-performance silicone for extremely long life and flexibility
- Simple connection thanks to premounted connectors
- Extraordinary design and high quality materials
- Toolless connection with the optional CONNECTsystem
- Easy mounting on many smooth surfaces thanks to self-adhesive tape at the back



Product family datasheet

Areas of application

- Cove lighting
- Wall integration
- Hand rails and corridors
- Machine lighting
- Path lighting
- Signage
- Suitable for outdoor use

Product family datasheet

Technical data

Electrical data

Product description	Nominal voltage	Type of current	Nominal wattage per meter	Rated wattage	Input voltage range	Accidental reverse input voltage protection up to
LF05A -B3-P ¹⁾	24.0 V	DC	7.3 W	72.00 W	23...25 V	25 V

¹⁾ See product remark

Photometrical data

Product description	Light color LED	Nominal dominant wavelength	Luminous flux per meter	Total useful luminous flux	Luminous efficacy	Standard deviation of color matching
LF05A -B3-P ¹⁾	Blue	467 nm	80 lm	840 lm	12 lm/W	≤3,5 sdc

Product description	Light color (designation)
LF05A -B3-P ¹⁾	Blue

¹⁾ See product remark

Light technical data

Product description	LED pitch	Beam angle	Rated beam angle (half peak value)	Starting time	Warm-up time (60 %)
LF05A -B3-P ¹⁾	20.0 mm	120 °	120.00 °	< 0.5 s	0.00 s

¹⁾ See product remark

LED module information

Product description	Number of LEDs per meter	Number of LEDs per smallest unit	Maximum operable length
LF05A -B3-P ¹⁾	50	5	9900 mm ²⁾

¹⁾ See product remark

²⁾ Max. cumulative product length powering it from a single end

Product family datasheet

Dimensions & weight

Product description	Length	Length – smallest unit	Width	Height	Cable length	Product weight
LF05A -B3-P ¹⁾	9900 mm ²⁾	100.0 mm	11.0 mm	4.5 mm	500.0	800.00 g

¹⁾ See product remark

²⁾ LED pitch 20 mm

Product line drawing



LF05A -B3-P

Colors & materials

Product description	Cover material	Body material
LF05A -B3-P ¹⁾	Silicone	Silicone

¹⁾ See product remark

Product family datasheet

Temperatures & operating conditions

Product description	Performance temp. acc. to IEC 62717	Temperature range in operation at T _c point	Ambient temperature range	Temperature range at storage
LF05A -B3-P ¹⁾	25 °C	-30...75 °C ²⁾	-20...+50 °C ³⁾	-40...+85 °C

¹⁾ See product remark

²⁾ At the T_c point

³⁾ Rated ambient temp. 25°C/Providing that temperature at T_c point is below max value during operation/Temperature ramping for environmental testing acc. to IEC 62717, 1K/min

Lifespan

Product description	Rated lamp life time	Nominal lamp life time	Lumen main. fact. at end of nom. life time	Number of switching cycles
LF05A -B3-P ¹⁾	50000 h ²⁾	50000 h	0.70	15000

¹⁾ See product remark

²⁾ L70/B50 at T_c 40 °C

Capabilities

Product description	Lowest bending radius
LF05A -B3-P ¹⁾	50 mm

¹⁾ See product remark

Certificates & standards

Product description	Energy consumption	Standards	Type of protection
LF05A -B3-P ¹⁾	80 kWh/1000h	CE	IP67

¹⁾ See product remark

Logistical data

Product description	Commodity code
LF05A -B3-P ¹⁾	940540399000

¹⁾ See product remark

Product family datasheet

Environmental information

Product description	Date of Declaration	Primary Article Identifier	Candidate List Substance 1
LF05A -B3-P ¹⁾	30-12-2021	4008321617804	No declarable substances contained

Product description	CAS No. of substance 1	Declaration No. in SCIP database
LF05A -B3-P ¹⁾	No CAS	No declarable substances contained

¹⁾ See product remark

Product remark

Modules perfectly matched to OSRAM OPTOTRONIC LED drivers (see relevant table)/For current photometric data and important safety, installation and application information (see www.osram.com/led-systems)/All the technical parameters apply to the entire module. In view of the complex manufacturing process for light emitting diodes, the typical values given above for the technical LED parameters are merely statistical values that do not necessarily correspond to the actual technical parameters of an individual product; individual products may vary from the typical values

Equipment / Accessories

- - Simplified connection with optional matching CONNECTsystem
 - Quick installation with optional SLIM TRACK System
 - Perfectly matched to OPTOTRONIC 24 V electronic control gears

Application advice

For more detailed application information and graphics please see product datasheet.

Product family datasheet

Additional product information

- Some LED modules are equipped with a self-adhesive tape for attaching the LED module to suitable materials, such as aluminum profiles, which must be clean and free of oil or silicone coatings, as well as other dirt/dust particles. The adhesive tape is intended for single use and if removed may damage the material to which it is stuck and the LED module itself, which must then be scrapped. Use the adhesive tape when the installation material temperature is in the 18 °C...35 °C range. Complete adhesion takes up to 72 h.
- LED modules are designed for static installations in accordance with IPC 6013C – Use A. Take material vibrations, repetitive torsion, and elongation/compression into account.
- If the operating environment covers a broad temperature range (e.g. outdoor applications) and the operating length is longer than 2 m, the use of adequate mounting surfaces is required. The use of an additional thicker adhesive tape between LED module and mounting surface is also recommended in order to absorb the stress of any mismatch in expansion. Assure enough space for module expansion with increasing temperature.
- The manufacturer is not responsible for damage due to chemical corrosion. The user must provide suitable protection against corrosive agents such as moisture and condensation and any other harmful elements/compounds. Make certain to avoid corrosive atmospheres. According to the current state of LED technology, hydrogen sulfide (H₂S) causes accelerated corrosion which leads to shortened lifetime or premature failure. Sources of H₂S may be rubber, foam rubber, soft-foam tapes, rubber-based sealing, natural sources (e.g. sulfur springs), etc. To avoid H₂S from sulfur-vulcanized rubber use silicon-based materials or peroxide-crosslinked rubber instead. Follow the recommendations in the material datasheet of the rubber supplier.
- IP00 LED modules, as manufactured, have no conformal coating and therefore offer no inherent protection against corrosion. Conformal coating treatment is possible, however materials must be selected properly in order to avoid product damage or impaired performance; the user must also completely seal the cut parts (ends/edges).
- For applications involving exposure to humidity and dust the module must be protected by a fixture or housing with a suitable IP protection class.
- Consult OSRAM Technical Service for further advice.
- Only a qualified electrician may install the module.
- Handle with care and ensure that there is no mechanical product damage, including damage to invisible internal electronics parts.
- Exceeding maximum operating and storage temperature ratings can reduce the expected lifetime or even destroy the LED module. The temperature of the LED module must be measured at the T_c-point in accordance with EN 60598-1 under steady-state conditions, considering the worst case; drive all channels at 100 % power. Refer to the product drawing for the exact location of the T_c-point.
- Exceeding the maximum ratings for the operating voltage causes hazardous overload and will likely destroy the LED module.
- Installation of LED modules and connection to the power supply must comply with all applicable electrical and safety standards.
- Observe correct polarity and wiring diagrams! Incorrect polarity or wrong wiring can cause unpredictable permanent damage or even failure of the product.
- Never exceed the maximum operable length, including daisy-chaining connections.
- Always ensure electrical isolation between the LED module and the mounting surface, especially in the vicinity of connections or cut ends.
- IP00 LED modules are ESD-sensitive; take adequate precautions during installation and operation of the products.
- Use only SELV LED drivers in accordance with applicable lighting standards and LED module ratings. In order to safely operate OSRAM LED modules it is necessary to supply them with an electronically stabilized power supply providing protection against short circuits, overload and overheating. To simplify the approval process of the luminaire/installation, the electronic power supplies control gear for LED modules must bear the CE and ENEC marking. In Europe the Declarations of Conformity must include at least the following standards: EN 61347-2-13, EN 55015, EN 61547 and EN 61000-3-2. ENEC certification will be based on EN 61347-2-13 and EN 62384. OSRAM OPTOTRONIC LED drivers comply with all relevant standards and guarantee safe operation; see the relevant brochure for more detailed information about OSRAM OPTOTRONIC.
- Avoid installations in rural and urban areas with high industrial activity and heavy traffic (higher than class than 4C1 according IEC 60721-3) and as well as installation in spa, areas with chlorine atmosphere, direct exposure to blown sand.

Sales and Technical Support





Product family datasheet

Sales and Technical Support www.osram.com

Country specific information

Product description	Product code	METEL code	SEG-No.	STK number	UK Org
LF05A -B3-P	4008321617804	OSRLF05AB3P	-	4031362	-
LF05A -B3-P	4008321617804	OSRLF05AB3P	-	4031362	-

Download Data

File	
	Product Datasheet 335842_LINEARlight Flex Protect LF05A-P (EN)
	Brochures Light is freedom of design (EN)
	Declarations of conformity 466011_EC-DoC LF05A-E-P
	Eulumdat 327873_LINEARlight Flex Protect LF05A-B3-P

Product family datasheet

Ecodesign regulation information:

ul>This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015. The contained light source is intended for use in applications requiring high-quality coloured light.

Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.

In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer.

In the contrary, and limited to the LINEARlight Flex Diffuse, LINEARlight Rigid Finesse, GINO LED Flex Diffuse and LUMINENT Milky product families, the contained light source is an integrated part of the containing product and its removal can only be done by causing a permanent damage to the containing product due to its tight mechanical, electrical, optical, thermal interaction and/or environmental protection with or from the containing product. Therefore, a replacement of the light source with the use of common available tools is not justified.

Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer.

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321617804	LF05A -B3-P	Shipping carton box 8	366 mm x 380 mm x 286 mm	39.78 dm ³	8971.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Accessories Optional

Product description	Accessory name	Accessory code
LF05A -B3-P	LF -2PIN Protect	▶ 4062172016513
LF05A -B3-P	LF -2CONN Protect	▶ 4062172016476
LF05A -B3-P	LF -ENDCAP Protect	▶ 4062172016438
LF05A -B3-P	LF-CLIP -FIXTURE PROTECT	▶ 4008321644749
LF05A -B3-P	LF-LTS -2100	▶ 4008321978981

Product family datasheet

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.